


VALVE FOR CHLORINE CYLINDERS

Product Features :

- * Body Material: (i) High Tensile Brass, as per IS 3224:2002, clause 5.2.1.1.2, Amd No 1
 (ii) Aluminium silicon bronze, as per IS 3224:2002, clause 5.2.1.1.1, Amd No 1
- * Spindle Material: Monel-400 as per IS 3224:2002 clause 5.2.1.2
- * CNC machined components ensure valve leak proof at minimum torque and long service life.





WRENCHING FLAT 30mm. CLOSING TORQUE OF SPINDLE < 12Nm OVER ALL HEIGHT (in close position) = 120mm App. SIZE OF OPERATING KEY = 9.5mm Sq.

Material of Construction : Material of Construction :

S.NO.	DESCRIPTION	MATERIAL	REMARKS	
1	VALVE HOUSING	HIGH TENSILE BRASS/ALUMINIUM SILICON BRONZE	IS 3224	
2	SPINDLE	MONEL METAL	IS 3224	
3	WASHER	BRASS	IS 319	
4	GLAND NUT	BRASS		
5	GLAND	BRASS	IS 319	
6	GLAND PACKING	TEFLON		
7	SEAL NUT	BRASS		
8	GASKET	LEAD		

Service Chart

Gas service	Test Pressure in Kgf/cm2		Outlet Connection as per IS 3224	
	Pneumatic	Hydraulic	Outlet No	Thread
Chlorine	35	55	5	G 5/8 A (External)